

easyTymp

Handheld Screening Tympanometer with Reflex Tests



- Very fast and reliable Impedance measurement
- Probe tone 226 Hz, optional high frequency probe tone 1 kHz
- Reflex frequencies 500 Hz, 1 kHz, 2 kHz, 4 kHz
- Automatic tests – self-explanatory to use
- Full color, high resolution display
- Stores more than 1000 measurements

easyTymp

Handheld Screening Tympanometer with Reflex Tests

Very fast middle ear measurements

The easyTymp is the ideal handheld device for middle ear screening tests. It performs reliable impedance and ipsilateral reflex tests within seconds.

The intensity of the four frequencies of the ipsilateral reflex test is increased automatically until a reflex is detected or the maximum is reached.

Select Protocol

All available test protocols can be easily selected with one hand. Available test protocols: Tympanometry with 226 Hz; Tympanometry and Auto Reflex or Tympanometry with Reflex at 90 dB.

Optional high frequency tympanometry

The optional high frequency probe tone of 1 kHz is ideal for providing reliable results when testing newborns and young children. Available test protocols: Tympanometry with 1 kHz; Tympanometry and Auto Reflex at 70 dB (Pure Tone) or Tympanometry with Reflex at 80 dB Broadband-Noise.

easyTymp cradle

The easyTymp cradle serves as a docking station and re-charger. It is available as a version with ear tip box or integrated printer.

Extensive Storage

The internal memory of the easyTymp stores more than 1000 measurements. With the impedance software data can also be transferred to a PC.

Standard Accessories

easyTymp handheld unit; with Probe tip; Probe Tip replacement; rechargeable battery; Power supply unit; Eartip box with eartips; Calibration cavity; Carrying case; MAICO-Impedance Software

Additional Accessories

- External Probe (35 cm)
- License for high frequency probe tone of 1 kHz
- Cradle with integrated ear tip box, power supply unit and additional rechargeable battery
- Cradle with integrated printer, power supply unit and additional rechargeable battery
- Power supply unit for easyTymp handheld unit
- Wall Mount Kit for cradle



easyTymp with cradle and eartip box

Technical Data

Tympanometer

Probe frequency, -intensity	226 Hz \pm 1%, 69 dB _{SPL} in 2 cm ³
Optional	1000 Hz \pm 1%, 69 dB _{SPL} in 2 cm ³
Pressure range	+ 200 to - 400 daPa
Volume range	0,1 to 8,0 ml
Accuracy	\pm 5% or \pm 10 daPa
Test time	< 3 seconds

Reflex Mode

Test frequencies	500, 1000, 2000, 4000 Hz \pm 3%
Test Method	ipsilateral
Intensities ipsilateral	70 ... 100 dB _{HL}
Intensity setting	automatic or single intensity

Test protocols

	Tymp 226 Hz;
	Tymp 226 Hz + Auto Reflex;
	Tymp 226 Hz + Reflex 90 dB
Opt. High Frequency	Tymp 1 kHz;
	Tymp 1 kHz + Auto Reflex;
	Tymp 1 kHz + Reflex 80 dB BB

easyTymp

Memory	1 curve per ear and test
Internal Memory	> 1000 measurements
Display	Full color graphic LCD-Display
Dimensions / Weight	W x D x H: 80 x 300 x 70 mm / 427 g

Cradle

Dimensions	B x T x H: 150 x 295 x 110 mm
Power	100 - 240 VAC, 50/60 Hz

Optional external Probe

Optional Printer	Probe with status lights
	4 Inch Thermo printer

Medical CE-mark Standards

IEC 60601-1, Class II,
Type B, IEC 60601-1-2
IEC 60645-5



Specifications are subject to change without notice



MAICO Diagnostic GmbH
Salzufer 13/14
10587 Berlin
Germany

Tel.: +49 30/70 71 46-50
Fax: +49 30/70 71 46-99
E-Mail: sales@maico.biz
Web: www.maico.biz